



(19) **United States**

(12) **Patent Application Publication**

Nguyen et al.

(10) **Pub. No.: US 2006/0259136 A1**

(43) **Pub. Date:** **Nov. 16, 2006**

(54) **HEART VALVE PROSTHESIS AND METHODS OF MANUFACTURE AND USE**

Publication Classification

(75) Inventors: **Than Nguyen**, Placentia, CA (US); **Hung Nguyen**, Garden Grove, CA (US); **Mykim Nguyen**, Santa Ana, CA (US); **Stanley Komatsu**, Laguna Hills, CA (US); **Robrecht Michiels**, Laguna Hills, CA (US)

(51) **Int. Cl.**
A61F 2/24 (2006.01)

(52) U.S. Cl. 623/2.18; 623/1.31

(57) **ABSTRACT**

A heart valve prosthesis is provided having a self-expanding multi-level frame that supports a valve body comprising a skirt and plurality of coating leaflets. The frame transitions between a contracted delivery configuration that enables percutaneous transluminal delivery, and an expanded deployed configuration having an asymmetric hourglass shape. The valve body skirt and leaflets are constructed so that the center of coaptation may be selected to reduce horizontal forces applied to the commissures of the valve, and to efficiently distribute and transmit forces along the leaflets and to the frame. Alternatively, the valve body may be used as a surgically implantable replacement valve prosthesis.


Correspondence Address:




**LUCE, FORWARD, HAMILTON & SCRIPPS
LLP
11988 EL CAMINO REAL, SUITE 200
SAN DIEGO, CA 92130 (US)**

(73) Assignee: **COREVALVE SA**, Paris (FR)

(21) Appl. No.: **11/128,826**

(22) Filed: **May 13, 2005**








FIG. 2




FIG. 3A




FIG. 3B




FIG. 5




FIG. 6

HEART VALVE PROSTHESIS AND METHODS OF MANUFACTURE AND USE

FIELD OF THE INVENTION

[0001] The present invention relates to replacement valves for improving the cardiac function of a patient suffering from cardiac valve dysfunction, such as aortic valve regurgitation or aortic stenosis. More particularly, the present invention relates to heart valve prostheses that provide improved durability and are particularly well-suited for percutaneous delivery.

BACKGROUND OF THE INVENTION

[0002] Heart valve replacement has become a routine surgical procedure for patients suffering from valve regurgitation or stenotic calcification of the leaflets. While certain procedures may be performed using minimally-invasive techniques (so-called "keyhole" techniques), the vast majority of valve replacements entail full sternotomy and placing the patient on cardiopulmonary bypass. Traditional open surgery inflicts significant patient trauma and discomfort, requires extensive recuperation times and may result in life-threatening complications.

[0003] To address these concerns, within the last decade efforts have been made to perform cardiac valve replacements using minimally-invasive techniques. In these methods, laparoscopic instruments are employed to make small openings through the patient's ribs to provide access to the heart. While considerable effort has been devoted to such techniques, widespread acceptance has been limited by the clinician's ability to access only certain regions of the heart using laparoscopic instruments.

[0004] Still other efforts have been focused on percutaneous transluminal delivery of replacement cardiac valves to solve the problems presented by traditional open surgery and minimally-invasive surgical methods. In such methods, a valve prosthesis is compacted for delivery in a catheter and then advanced, for example, through an opening in the femoral artery and through the descending aorta to the heart, where the prosthesis then is deployed in the aortic valve annulus. Although transluminal techniques have attained widespread acceptance with respect to delivery of stents to restore vessel patency, only mixed results have been obtained with respect to percutaneous delivery of relatively more complicated valve prostheses.

[0005] One such example of a previously-known device heart valve prosthesis is described in U.S. Pat. No. 6,454,799 to Schreck. The prosthesis described in that patent comprises a fabric-based heart valve disposed within a plastically deformable wire-mesh base, and is delivered via expansion of a balloon catheter. One drawback with balloon catheter delivery of the prosthetic valve is that the valve leaflets may be damaged when compressed between the balloon and the base during deployment. In addition, because balloon expandable structures tend to experience some recoil following balloon deflation, perivalvular leaks may develop around the circumference of the valve prosthesis.

[0006] Accordingly it would be desirable to provide a percutaneously-deliverable valve prosthesis that reduces the risk of leaflet damage during deployment of the prosthesis.

It further would be desirable to provide a valve prosthesis that reduces the risk of perivalvular leaks resulting from recoil of the prosthesis following deployment.

[0007] U.S. Pat. No. 6,027,525 to Suh, et al. describes a valve prosthesis comprising a series of self-expanding units affixed to a polymeric cover and having a valve disposed therein. Such devices are not suitable for cardiac valve replacement because of the limited ability to compact the valve disposed within the prosthesis. Moreover, such valve prostheses would be particularly undesirable for treating aortic valve defects, because the polymeric cover would obscure the ostia of the coronary arteries, both disrupting blood flow to the coronary arteries and preventing subsequent catheterization of those arteries. Accordingly, it would be desirable to provide a valve prosthesis that is self-expanding, yet permits the valve to be compacted to a greater degree than previously-known designs.

[0008] U.S. Pat. No. 6,682,559 to Myers, et al. also describes a valve prosthesis having an essentially tubular design. One drawback of such configurations is that relatively large horizontal forces arise along the coaptation edges of the leaflets and are transmitted to the commissural points. These forces may adversely affect the durability of the leaflets and lead to valve failure. In view of this, it would be desirable to provide a valve wherein the center of coaptation of the leaflets may be selected so as to reduce horizontal forces applied to coaptation edges of the leaflets and commissural points, thereby improving durability of the valve. In addition, it would be desirable to provide a valve design that more uniformly distributes horizontal forces over the coaptation edges of the leaflets, rather than concentrating those forces at the commissural points.

[0009] In an effort to more nearly recreate the force distribution along the leaflets of natural tissue valves, some previously-known valve designs include circular base portions having longitudinal projections that function as anchors for the commissural points, such as described in U.S. Pat. No. 5,855,601 to Bessler, et al. and U.S. Pat. No. 6,582,462 to Andersen, et al.

[0010] While the valve prostheses of Bessler and Andersen may be readily collapsed for delivery, those designs are susceptible to problems once deployed. For example, the longitudinal projections of such prostheses may not provide sufficient rigidity to withstand compressive forces applied during normal movements of the heart. Deformation of the commissural anchors may result in varied forces being imposed on the commissures and leaflets, in turn adversely impact functioning of the leaflets. In addition, because the exteriors of the foregoing valve prostheses are substantially cylindrical, the prostheses are less likely to adequately conform to, and become anchored within the valve annulus anatomy during deployment. As a result, cyclic loading of the valve may result in some slippage or migration of the anchor relative to the patient's anatomy.

[0011] In view of the foregoing, it would be desirable to provide a valve that is capable of conforming to a patient's anatomy while providing a uniform degree of rigidity and protection for critical valve components. It therefore would be desirable to provide a valve prosthesis having portions that are capable of deforming circumferentially to adapt to the shape of the pre-existing valve annulus, but which is not susceptible to deformation or migration due to normal

movement of the heart. Still further, it would be desirable to provide a valve prosthesis having a multi-level component that is anatomically shaped when deployed, thereby enhancing anchoring of the valve and reducing the risk of migration and perivalvular leaks.

SUMMARY OF THE INVENTION

[0012] In view of the foregoing, it is an object of the present invention to provide a valve prosthesis that overcomes the drawbacks of previously-known designs, and which may be implanted using open surgical, minimally invasive or percutaneous implantation techniques.

[0013] It is also an object of the present invention to provide a percutaneously-deliverable valve prosthesis that reduces the risk of leaflet damage during deployment of the prosthesis.

[0014] It is a further object of this invention to provide a valve prosthesis that reduces the risk of perivalvular leaks resulting from elastic recoil of the prosthesis following deployment.

[0015] It is another object of the present invention to provide a valve prosthesis that is self-expanding, yet permits the valve to be compacted to a greater degree than previously-known designs and permits ready access to adjoining anatomical structures, such as the coronary arteries.

[0016] It is a still further object of the present invention to provide a valve in which the center of coaptation of the leaflets may be selected so as to reduce horizontal forces applied to coaptation edges of the leaflets and commissural points, thereby improving durability of the valve.

[0017] In addition, it is an object of this invention to provide a valve design that more uniformly distributes forces over the coaptation edges of the leaflets, rather than concentrating those forces at the commissural points.

[0018] It is yet another object of this invention to provide a valve that is anatomically shaped, provides a uniform high degree of rigidity and protection for critical valve components, and which is less susceptible to deformation arising from normal movement of the heart.

[0019] It is an object of the present invention to provide a valve prosthesis having portions that are capable of deforming circumferentially to adapt to the shape of the pre-existing valve annulus, but which is not susceptible to deformation or migration due to normal movement of the heart.

[0020] It is also an object of this invention to provide a valve prosthesis having a multi-level component that is anatomically shaped when deployed, thereby enhancing anchoring of the valve and reducing the risk of migration and perivalvular leaks.

[0021] It is a further object of the present invention to provide a valve prosthesis wherein a valve is disposed within a rigid portion of a multilevel frame, so that valve area and function are not impaired, but inflow and/or outflow portions of the multilevel frame are capable of conforming to patient anatomy anomalies.

[0022] It is a further object of the present invention to provide a valve prosthesis that facilitates alignment of the heart valve prosthesis with the direction of blood flow.

[0023] These and other objects of the present invention are accomplished by providing a heart valve prosthesis wherein a self-expanding multi-level frame supports a valve body comprising a skirt and plurality of coapting leaflets. The frame has a contracted delivery configuration, in which the prosthesis may be stored within a catheter for percutaneous delivery, and an expanded deployed configuration having an asymmetric hourglass shape. The valve body skirt and leaflets preferably are constructed of porcine, bovine, equine or other mammalian tissue, such as pericardial tissue, and are sewn, welded, molded or glued together so as to efficiently distribute forces along the leaflets and to the frame. Alternatively, the valve body may comprise a synthetic or polymeric material.

[0024] In accordance with the principles of the present invention, the frame comprises multiple levels, including a proximal conical inflow section, a constriction region and a flared distal outflow section. Each of the inflow and outflow sections is capable of deforming to a non-circular cross-section to conform to the patient's anatomy, while the constriction region is configured to retain a circular cross-section that preserves proper functioning of the valve body.

[0025] The frame comprises a plurality of cells having a pattern that varies along the length of the frame to provide a high degree of anchoring and alignment of the valve prosthesis. The cell pattern further is selected to provide a uniform diameter where the commissural joints of the leaflets are attached to the frame, while permitting the inflow and outflow regions to expand to conform to the patient's anatomy. In this manner, optimal functioning of the valve body may be obtained even though the frame may be deployed in anatomies having a range of sizes. In addition, the frame resists deformation caused by movement of the heart and enables a functional portion of the valve body to be disposed supra-annularly to the native valve, with a portion of the valve prosthesis extending into the native valve annulus.

[0026] In one embodiment suitable for aortic valve replacement, the valve body comprises a skirt coupled to three leaflets. Each of the components preferably is formed of animal pericardial tissue or synthetic material, and then sewn, glued, welded or molded together. The lateral ends of the leaflets include enlarged regions that are folded to both form the commissural joints and fasten the commissural joints to the frame. The skirt and leaflets further are configured so that the joints align with contours of the cell pattern of the frame.

[0027] In a preferred embodiment, the commissural joints are affixed to the frame at locations above the area of coaptation, to provide a selectable center of coaptation of the leaflets. This design provides a more efficient delivery configuration because the commissures are not compressed against the leaflets when the valve prosthesis is reduced to the contracted delivery configuration. Additionally, by lengthening the distance to the commissures, the design mimics the functioning of natural tissue valves by distributing forces along the coaptation edges and reducing horizontal forces transmitted to the commissural joints.

[0028] In alternative embodiments, the valve body of the present invention may include a sewing ring in lieu of the frame to facilitate surgical implantation, and may employ as few as two and as many as four leaflets.

[0029] Methods of making and using the valve prostheses of the present invention are also provided.

BRIEF DESCRIPTION OF THE DRAWINGS

[0030] The above and other objects and advantages of the present invention will be apparent upon consideration of the following detailed description, taken in conjunction with the accompanying drawings, in which like reference numerals refer to like parts throughout, and in which:

[0031] **FIGS. 1A, 1B and 1C** are, respectively, side and top end views of an exemplary valve prosthesis of the present invention in the expanded deployed configuration and an enlarged region of the frame of the valve prosthesis;

[0032] **FIG. 2** is a side view of the frame of the valve prosthesis of **FIGS. 1** in a contracted delivery configuration;

[0033] **FIGS. 3A and 3B** are, respectively, plan views of a leaflet and the skirt employed in the valve body of the present invention;

[0034] **FIGS. 4A and 4B** are, respectively, a perspective view of a leaflet with its enlarged regions folded, and a plan view of the valve body of the present invention, wherein the leaflets are fastened to the skirt;

[0035] **FIG. 5** is a side view of the valve body of **FIG. 4B** fully assembled; and

[0036] **FIG. 6** is a side view depicting the valve prosthesis of the present invention deployed atop a patient's aortic valve.

DETAILED DESCRIPTION OF THE INVENTION

[0037] The present invention is directed to a heart valve prosthesis having a self-expanding frame that supports a valve body. In a preferred embodiment, the frame has a tri-level asymmetric hourglass shape with a conical proximal section, an enlarged distal section and a constriction region having a predefined curvature when the frame is deployed. In the context of the present application, the proximal section constitutes the "inflow" portion of the valve prosthesis and is disposed in the aortic annulus of the patient's left ventricle, while the distal section constitutes the "outflow" portion of the valve prosthesis and is positioned in the patient's ascending aorta.

[0038] In a preferred embodiment the valve body comprises three leaflets that are fastened together at enlarged lateral end regions to form commissural joints, with the unattached edges forming the coaptation edges of the valve. The leaflets are fastened to a skirt, which is in turn affixed to the frame. The enlarged lateral end regions of the leaflets permit the material to be folded over to enhance durability of the valve and reduce stress concentration points that could lead to fatigue or tearing of the leaflets. The commissural joints are mounted above the plane of the coaptation edges of the valve body to minimize the contracted delivery profile of the valve prosthesis, while the configuration of the edges permits uniform stress distribution along the coaptation edges.

[0039] Referring to **FIGS. 1**, an exemplary embodiment of a valve prosthesis constructed in accordance with the principles of the present invention is described. Valve prosthesis

10 comprises expandable frame **12** having valve body **14** affixed to its interior surface, e.g., by sutures. Frame **12** preferably comprises a self-expanding structure formed by laser cutting or etching a metal alloy tube comprising, for example, stainless steel or a shape memory material such as nickel titanium. The frame has an expanded deployed configuration which is impressed upon the metal alloy tube using techniques that are per se known in the art. Valve body **14** preferably comprises individual leaflets assembled to a skirt, where all of the components are formed from a natural or man-made material. Preferred materials for valve body **14** include mammalian tissue, such as porcine, equine or bovine pericardium, or a synthetic or polymeric material.

[0040] Frame **12** preferable includes multiple levels, including outflow section **15**, inflow section **16** and constriction region **17**. As depicted in the enlarged view of **FIG. 1B**, the frame comprises a plurality of cells having sizes that vary along the length of the prosthesis. As indicated by dotted lines a, b and c, each cell comprises two zig-zag structures having unequal-length struts, wherein the vertices of the zig-zags are coupled together. For example, zig-zag **18** has length z_1 whereas zig-zag **19** has greater length z_2 . This cell design permits each level of cells between the proximal and distal ends of the frame to be tailored to meet specific design requirements, such as, compressibility, expansion characteristics, radial strength and so as to define a suitable contour for attachment of the valve body.

[0041] The cell pattern of frame **12** also enables the frame to expand to the tri-level asymmetric hourglass shape depicted in **FIG. 1A**, having conical inflow section, enlarged outflow section and fixed diameter constricted region. Each section of frame **12** has a substantially circular cross-section in the expanded deployed configuration, but in addition the cell patterns of the inflow and outflow sections permit those sections to adapt to the specific anatomy of the patient, thereby reducing the risk of migration and reducing the risk of perivalvular leaks. The cell patterns employed in the constriction region are selected to provide a uniform circular cross-section area for the constriction region when deployed, and a pre-determined radius of curvature for the transition between the constriction region and outflow section of the frame. In particular, the convex-concave shape of frame **12** within the constriction region ensures that the frame is held away from the opposing sinus wall in the ascending aorta, thus ensuring adequate blood flow to the coronary arteries and facilitating catheter access to the coronary arteries.

[0042] Enlarged outflow section has nominal deployed diameter D_o , inflow section has nominal deployed diameter D_i , and constriction region has deployed substantially fixed diameter D_c . The conical shape of the inflow region and smooth transitions between adjacent sections of frame **12** are expected to be particularly advantageous in directing blood flow through the valve body with little or no turbulence, as compared to step changes in diameter observed for surgically implanted replacement valves.

[0043] The above-described cell pattern permits each of the inflow and outflow sections of frame **12** to expand to a diameter within a range of deployed diameters, while retaining constriction region **17** at a substantially constant diameter. Thus, for example, outflow diameter D_o may range from 30 to 55 mm, while inflow diameter D_i may vary from

19 to 34 mm. Illustratively, frame **12** may be manufactured in four sizes having a range of diameters D_o , D_i and D_c as set forth in Table 1 below:

TABLE 1

	Size A	Size B	Size C	Size D
D_o	40 mm	50 mm	40 mm	50 mm
D_c	22 mm	22 mm	24 mm	24 mm
D_i	26 mm	26 mm	29 mm	29 mm

[0044] Advantageously, these four frame sizes are expected to cover a wide range of patient anatomies, while requiring construction of only two sizes of valve bodies (22 and 24 mm). Compared to previously-known commercially available surgical valves, which vary from approximately 17 mm to 31 mm in one millimeter increments, it is expected that the above four sizes of valve prosthesis of the present invention could be used for more than 75% of the patient population, thus greatly reducing the costs associated with manufacturing and inventorying large numbers of parts.

[0045] When configured as a replacement for an aortic valve, inflow section **16** extends into and anchors within the aortic annulus of a patient's left ventricle and outflow section **15** is positioned in the patient's ascending aorta. Importantly, the configuration of outflow section **15** is expected to provide optimal alignment of the valve body with the direction of blood flow. In addition, the cell pattern of outflow section **15** also serves to anchor the outflow section in the patient's ascending aorta to prevent lateral movement or migration of frame **12**. As depicted in FIG. 1C, the use of relatively larger cells in the outflow section of frame **12**, combined with the convex-concave shape of constriction region **17**, ensures that the frame does not obstruct blood flow to the patient's coronary arteries when deployed and allows for catheter access to the coronary arteries. Frame **12** also may include eyelets **20** for use in loading the heart valve prosthesis **10** into a delivery catheter.

[0046] Still referring to FIGS. 1, valve body **14** includes skirt **21** affixed to frame **12**, and leaflets **22**. Leaflets **22** are attached along their bases to skirt **21**, for example, using sutures **23** or a suitable biocompatible adhesive. Adjoining pairs of leaflets are attached to one another at their lateral ends to form commissures **24**, with free edges **25** of the leaflets forming coaptation edges that meet in area of coaptation **26**.

[0047] As depicted in FIG. 1A, the curve formed at joint **27** between the base of each leaflet **22** and skirt **21** follows the contour of the cell pattern of frame **12**, so that most of the length of joint **27** is directly supported by frame **12**, thereby transmitting forces applied to the valve body directly to the frame. As further depicted in FIG. 1C, commissures **24** are configured to span a cell of frame **12**, so that force is evenly distributed within the commissures and to frame **12**.

[0048] Referring to FIG. 2, valve prosthesis **10** is shown in the contracted delivery configuration. In this state, valve prosthesis may be loaded into a catheter for percutaneous transluminal delivery via a femoral artery and the descending aorta to a patient's aortic valve. In accordance with one aspect of the present invention, commissures **24** are dis-

posed longitudinally offset from coaptation edges **25** of the valve body, thereby permitting a smaller delivery profile than achievable with previously-known replacement valves. In addition, because frame **12** self-expands upon being released from the delivery catheter, there is no need to use a balloon catheter during placement of valve prosthesis **10**, thereby avoiding the potential for inflicting compressive injury to the valve leaflets during inflation of the balloon.

[0049] Referring now to FIGS. 3A and 3B, skirt **21** and leaflet **22** of a preferred aortic valve embodiment of the present invention are described. Skirt **21** and leaflet **22** preferably are cut from a sheet of animal pericardial tissue, such as porcine pericardial tissue, or synthetic or polymeric material, either manually or using a die or laser cutting system. The pericardial tissue may be processed in accordance with tissue processing techniques that are per se known in the art for forming and treating tissue valve material. Alternatively, skirt **21** and leaflet **22** may be constructed on a synthetic or polymeric material. In a preferred embodiment, skirt **21** and leaflets **22** have a thickness of between 0.008" and 0.016", and more preferably between 0.012" and 0.014".

[0050] Leaflet **22** includes enlarged lateral ends **30** and **31** disposed at either end of free edge **32**, and body **33**. Free edge **32** forms coaptation edge **25** of the finished valve body **14**, while lateral ends **30** and **31** are folded and joined to adjacent leaflets to form commissures **24**. In accordance with one aspect of the present invention, free edges **32** assume the form of catenaries when the valve body is affixed to frame **12**, thereby providing uniform loading along the length of the coaptation edge in a manner similar to a suspension bridge. Body **33** is joined to skirt **21** as described below. Lateral ends **30** and **31** illustratively are shown in FIG. 3A as having fold lines d, e and f, to define flaps **34**, **35** and **36**.

[0051] Skirt **21** preferably is constructed from the same material as leaflets **22**, and includes scalloped areas **37**, reinforcing tabs **38** and end tabs **39**. Each scalloped area **37** is joined to a body **33** of a respective leaflet **22**. Reinforcing tabs **38** illustratively include fold lines g, h and i, except for reinforcing tabs **40** and **41** at the lateral ends of the skirt, which have only one fold apiece. As described below, reinforcing tabs **40** and **41** are joined to one another, e.g., by sutures or gluing, so that skirt **21** forms a frustum of a cone.

[0052] End tabs **39** are folded over the ends of the proximal-most row of cells of frame **12** to secure skirt **21** to the frame and seal against perivalvular bypass flows (see FIG. 1A). Because end tabs **39** are directly supported by the last zig-zag row of cells of frame **12**, there is no opportunity for an unsupported edge of the skirt to flap or otherwise extend into the flow path along the inflow edge of skirt **21**. Thus, the design of the valve prosthesis not only ensures that there are no flaps to disrupt flow or serve as sites for thrombus formation, but also reduces the risk that hemodynamic flow against such flaps could cause frame **12** to migrate.

[0053] Referring to FIGS. 4A and 4B, assembly of valve body **14** from skirt **21** and leaflets **22** is described. In FIG. 4A, flap **34** first is folded along line d. Flap **35** is folded along line e so that it lies atop flap **34**, forming seam **42** comprising a triple thickness of the tissue. Flap **36** then is folded along line f. Adjoining leaflets **22** then are fastened together along adjacent seams **42**, resulting in a leaflet assembly.

[0054] Reinforcing tabs 38 are folded along lines g, h and i to form seams 43 comprising a double thickness of tissue. Next, the leaflet assembly is attached to skirt 21 along the bottom edges of bodies 33 of the leaflets to form joints 44. At this stage of the assembly, prior to attaching reinforcing tab 40 to 41 and the remaining seam 43 of leaflets 22, the valve body appears as depicted in FIG. 4B. Reinforcing tabs 40 and 41 then are fastened together to form another seam 43 along skirt 21 and the remaining seam 43 between leaflets 22. Valve body 14 then is ready to be affixed to frame 12.

[0055] Referring to FIG. 5, valve body 14 is shown as it would appear when affixed to frame 12, but with frame 12 omitted to better illustrate where the valve body is affixed to the frame. During the step of affixing the valve body to the frame, flaps 36 of adjacent leaflets are affixed, e.g., by sutures, to span a cell of the frame to support commissures 24 (compare to FIG. 1B) and end tabs 39 are folded over and affixed to the proximal-most row of cells of the frame 12 (compare to FIG. 1A). Valve body 14 also is attached to frame 12 along seams 43 formed by the reinforcing tabs. Each joint 44 is aligned with and fastened to (e.g., by sutures or glue) to a curved contour defined by the struts of the cells of frame 12, so that joint 44 is affixed to and supported by frame 12 over most of the length of the joint. As discussed above, the configuration of the cells in frame 12 may be specifically customized define a curved contour that supports joints 44 of the valve body.

[0056] When completely assembled to frame 12, valve body 14 is affixed to frame 12 along the edges of flaps 36 of the commissures, end tabs 39, leaflet seams 42, reinforcing tab seams 43 and joints 44. In this manner, forces imposed on leaflets 22, commissures 24 and joints 44 are efficiently and evenly distributed over the valve body and transferred to frame 12, thus reducing stress concentration and fatigue of the valve body components. Moreover, the use of multiple thicknesses of material along seams 42 and 43 is expected to provide a highly durable valve body which will last for many years once implanted in a patient.

[0057] In accordance with another aspect of the present invention, the center of coaptation of leaflets 22 is a distance L below the point at which the commissures are affixed to the frame, as shown in FIG. 5. Compared to previously-known designs, in the present invention the overall lengths of the coaptation edges are increased, while leaflets 22 coapt along a shorter portion of those lengths. Several advantages arise from this design:

[0058] the leaflets require only minimal pressure to open and have a rapid closing time.

[0059] the valve demonstrates better washing dynamics when open, i.e., less turbulence along the free edges of the leaflets.

[0060] the valve provides a more uniform distribution of stresses along the coaptation edges of leaflets 22.

[0061] the angle at which force is transmitted to the commissures is increased, thereby substantially reducing the horizontal forces applied to the commissures that tend to pull the commissures away from the frame.

[0062] controlling the center of the height of coaptation allows the commissures to be located proximal of the center of coaptation, thereby reducing the contracted delivery profile of the valve prosthesis.

[0063] All of the foregoing benefits are expected to reduce non-uniform loads applied to the valve body, and substantially enhance the durability of the valve prosthesis.

[0064] As will of course be apparent to one of skill in the art of prosthetic valve design, the assembly steps described above are merely illustrative, and a different order of assembling the leaflets and skirt to form valve body 14 may be employed. In an alternative embodiment, a conventional sewing ring may be attached to valve body 14 and frame 12 may be omitted. In this case, the valve prosthesis may be implanted surgically, rather than by percutaneous transluminal delivery. In this case, commissures 24 may be attached to the ascending aorta by sutures or other means as described above.

[0065] Referring now to FIG. 6, implantation of valve prosthesis 10 of the present invention is described. As discussed above, valve prosthesis preferably comprises a self-expanding multilevel frame that may be compressed to a contracted delivery configuration, as depicted in FIG. 3, onto an inner member of a delivery catheter. The valve prosthesis and inner member may then be loaded into a delivery sheath of conventional design, e.g., having a diameter of less than 20-24 French. Due in part to the fact that commissures 24 are longitudinally offset from the coaptation edges of the leaflets, and also due to the ability to customize the cell pattern along the length of the frame, it is expected that valve prosthesis may be designed to achieve a significantly smaller delivery profile than previously-known percutaneously-deliverable replacement valves.

[0066] The delivery catheter and valve prosthesis are then advanced in a retrograde manner through a cut-down to the femoral artery and into the patient's descending aorta. The catheter then is advanced, under fluoroscopic guidance, over the aortic arch, through the ascending aorta and mid-way across the defective aortic valve. Once positioning of the catheter is confirmed, the sheath of the delivery catheter may be withdrawn proximally, thereby permitting the valve prosthesis to self-expand.

[0067] As the valve prosthesis expands, it traps leaflets LN of the patient's defective aortic valve against the valve annulus, retaining the native valve in a permanently open state. As further illustrated in FIG. 6, outflow section 15 of the valve prosthesis expands against and aligns the prosthesis within the ascending aorta, while inflow section 16 becomes anchored in the aortic annulus of the left ventricle, so that skirt 21 reduces the risk of perivalvular leaks.

[0068] As also seen in FIG. 6, the deployed configuration of constriction region 17 holds valve body 14 in a superannular position, away from the heart walls, thereby ensuring that the constriction region expands to the predetermined fixed diameter. This in turn ensures that the valve body does not experience any unexpected lateral loads and therefore expands to its design diameter, e.g., illustratively either 22 or 24 mm as in Table 1 above.

[0069] Because outflow section 15 of frame 12 employs relatively larger cells than the remainder of the frame, valve prosthesis 10 does not disrupt blood flow into coronary arteries CA when deployed, and also does not obstruct subsequent catheter access to the coronary arteries. Accordingly, a clinician may readily gain access to the coronary arteries, for example, to perform angioplasty or stenting,

simply by directing the angioplasty or stent delivery system guide wire through the openings in the cell pattern of frame 12.

[0070] While preferred embodiments of the invention are described above, it will be apparent to one skilled in the art that various changes and modifications may be made. The appended claims are intended to cover all such changes and modifications that fall within the true spirit and scope of the invention.

What is claimed is:

1. A valve prosthesis comprising:
 - a self-expanding multi-level frame having a contracted delivery configuration and an expanded deployed configuration, the multi-level frame having in the expanded deployed configuration an enlarged outflow section with a first nominal diameter, a conical inflow section having a second nominal diameter and a constriction region having a third fixed diameter smaller than the first and second nominal diameters; and
 - a valve body affixed to the multi-level frame, the valve body comprising a plurality of leaflets affixed to a skirt.
2. The valve prosthesis of claim 1 wherein the multi-level frame comprises a cell pattern defined by unequal length zig-zags.
3. The valve prosthesis of claim 1 wherein the conical section has a proximal end and the conical section flares outward towards the proximal end.
4. The valve prosthesis of claim 1 wherein adjoining leaflets are affixed together to form commissures and have free edges that define coaptation edges and a center of coaptation, the commissures being longitudinally offset from the center of coaptation.
5. The valve prosthesis of claim 4 wherein the commissures are affixed to the multi-level frame at a location proximal of the center of coaptation.
6. The valve prosthesis of claim 5 wherein the multi-level frame comprises a cell pattern and the commissures include flaps that span an entire area of at least one cell of the cell pattern.
7. The valve prosthesis of claim 4 wherein the commissures and coaptation edges of the leaflets define catenaries that substantially uniformly distribute loads over the leaflets.
8. The valve prosthesis of claim 7 wherein the catenaries are configured to reduce horizontal loads applied to the commissures.
9. The valve prosthesis of claim 1 wherein the leaflets are affixed to the skirt at joints, and the joints are affixed to the frame to evenly distribute forces through the valve body to the multi-level frame.
10. The valve prosthesis of claim 9 wherein the multi-level frame further comprises a cell pattern that defines a contour configured to support the joints.
11. The valve prosthesis of claim 4 wherein each leaflet is individually formed and comprises an enlarged lateral end having a plurality of flaps that are folded over to increase the durability of the commissures.
12. The valve prosthesis of claim 1 wherein the skirt further comprises a plurality of longitudinally-oriented reinforcing tabs.
13. The valve prosthesis of claim 12 wherein the reinforcing tabs are affixed to the multi-level frame.

14. The valve prosthesis of claim 12 wherein the skirt further comprises a plurality of end tabs adapted to be affixed to a proximal-most row of cells of the multi-level frame.

15. The valve prosthesis of claim 1 wherein the leaflets comprise a material selected from one of: porcine, bovine, equine or other mammalian pericardial tissue, synthetic material or polymeric material.

16. The valve prosthesis of claim 1 wherein the valve body is deployed superannularly of a patient's aortic annulus when the valve prosthesis is delivered within a patient's aortic valve and the multi-level frame is in the expanded deployed configuration.

17. The valve prosthesis of claim 1 wherein the multi-level frame is configured to hold a patient's native valve permanently open in the expanded deployed configuration.

18. The valve prosthesis of claim 1 wherein the multi-level frame is configured to permit access to a patient's coronary arteries in the expanded deployed configuration.

19. The valve prosthesis of claim 1 wherein multi-level frame has proximal and distal ends and a plurality of cell patterns that vary in size between the proximal and distal ends.

20. The valve prosthesis of claim 1 wherein the constriction region comprises a plurality of cell patterns configured to provide a pre-determined radius of curvature for a transition from the constriction region to the outflow section.

21. A valve prosthesis comprising:

a valve body comprising a plurality of leaflets affixed to a skirt, adjoining leaflets affixed together to form commissures and having free edges that define coaptation edges and a center of coaptation,

wherein the commissures are longitudinally offset from the center of coaptation and define catenaries that substantially uniformly distribute loads over the leaflets.

22. The valve prosthesis of claim 21 wherein the catenaries are configured to reduce horizontal loads applied to the commissures.

23. The valve prosthesis of claim 21 wherein each leaflet is individually formed and comprises an enlarged lateral end having a plurality of flaps that are folded over to increase the durability of the commissures.

24. The valve prosthesis of claim 21 wherein the skirt further comprises a plurality of longitudinally-oriented reinforcing tabs.

25. The valve prosthesis of claim 21 wherein the leaflets comprise a material selected from one of: porcine, bovine, equine or other mammalian pericardial tissue, synthetic material or polymeric material.

26. The valve prosthesis of claim 21 wherein the valve prosthesis further comprises a self-expanding frame, the leaflets are affixed to the skirt at joints, and the joints are affixed to the frame to evenly distribute forces through the valve body to the frame.

27. The valve prosthesis of claim 26 wherein the frame further comprises a cell pattern that defines a contour configured to support the joints.

28. The valve prosthesis of claim 24 wherein the valve prosthesis further comprises a self-expanding frame and the reinforcing tabs are affixed to the frame.

29. The valve prosthesis of claim 21 further comprising a self-expanding frame having a contracted delivery configuration and an expanded deployed configuration.

30. The valve prosthesis of claim 29 wherein the frame comprises a cell pattern defined by unequal length zig-zags.

31. The valve prosthesis of claim 29 wherein the commissures are affixed to the frame at a location proximal of the center of coaptation.

32. The valve prosthesis of claim 29 wherein the frame comprises a cell pattern and the commissures include flaps that span an entire area of at least one cell of the cell pattern.

33. The valve prosthesis of claim 29 wherein the skirt further comprises a plurality of end tabs adapted to be affixed to a proximal-most row of cells of the frame.

34. The valve prosthesis of claim 29 wherein the valve body is deployed superannularly of a patient's aortic annulus when the valve prosthesis is delivered within a patient's aortic valve and the frame is in the expanded deployed configuration.

35. The valve prosthesis of claim 29 wherein the frame is configured to hold a patient's native valve permanently open in the expanded deployed configuration.

36. The valve prosthesis of claim 29 wherein the frame is configured to permit access to a patient's coronary arteries in the expanded deployed configuration.

37. The valve prosthesis of claim 29 wherein frame has proximal and distal ends and a plurality of cell patterns that vary in size between the proximal and distal ends.

38. The valve prosthesis of claim 29 wherein the frame has, in the expanded deployed configuration, an enlarged outflow section with a first nominal diameter, a conical inflow section having a second nominal diameter and a constriction region having a third fixed diameter smaller than the first and second nominal diameters.

39. The valve prosthesis of claim 38 wherein the conical section has a proximal end and the conical section flares outward towards the proximal end.

40. The valve prosthesis of claim 38 wherein the constriction region comprises a plurality of cell patterns configured to provide a pre-determined radius of curvature for a transition from the constricted region to the outflow section.

* * * * *